

WD8260

80MM Thermal Receipt Printer



Features

- Support multi languages.
- Cash drawer drive supported.
- Compatible with ESC/POS print instruction set.
- Support IAP online upgrade and black mark upgrade.
- Optional interface: USB/ USB+Lan/ USB+BT/USB+WIFI+USB+WIFI,etc
- Support LED indicator light and prompt buzzer function.
- Excellent waterproof, anti-oil, anti-dust structure design.
- Support download and print logo & graphics. Support 1D,2D bar code printing.
- No ink cartridge or ribbon required, low operation cost, thermal paper is easy to buy.
- Characters can be amplified, printed in bold optionally, and line spacing printing can be adjusted.
- Can be widely used in manufacturing & warehouse logistic industry, healthcare, parcel post, office & studio, retail & etc.



Specifications

Product Specification

Interfaces :	USB/ USB+Lan/ USB+BT/USB+WIFI/USB+RS232,etc
Print Comand :	ESC/POS
Print Method :	Thermal Line Printing
Print Speed :	230mm/sec; 260mm/sec
No. of Total Dots :	576 dots/line
Auto Paper Cutter :	Full or Partial cut
Print Width :	80mm
NV Flash :	256K bytes
Compatible OS :	Window Systems ; Linux, Android & IOS Operate Systems
Character size :	ANK Font A: 12 x 24 dots; Font B: 9 x 17 dots Simplified/Traditional Chinese: 24 x 24 dots
Code :	1D:UPC1-/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128 2D: QR CODE/PDF417

Paper & Electrical

Type :	Roll Paper
Width :	79.5±0.5mm
Line spacing :	3.75mm(Adjustable by commands)
Roll Diameter :	83mm
Paper Thickness :	0.06-0.08mm
Power adaptor :	Input: AC:240-100V, 50-60Hz Output:DC 24V/2.5A
Cash Drawer Control :	12V/1A
Cutter life :	1.5 million cuts
Print Head :	Reliability
Print Reliability :	150km



WDLINK

Physical & Environmental

Temperature:	-10°C to 45 °C (work): - 20 °C to 60 °C (storage)
Humidity Working	10% - 90%
Warantty :	12 months at least
Weight:	0.85 Kg
Dimensions	137.2*133.5*177mm(D*W*H)

Product Pictures



WDLINK